

TUBULAR LED 25



Garanzia / Warranty: 5 anni

Temperatura d'esercizio: -20/+40
Operating temperature

CRI ; tolleranza colore (SDCM): >80 ; Max 3 step MacAdam
CRI ; color difference

Classe di sicurezza fotobiologica: Group 0
Photobiological compliance

Classe energetica: A+
Energetic class

Norme di riferimento: EN55015, EN61000-3-2, EN61000-4-2,
Main references EN61000-4-3, EN61000-4-4, EN61000-4-5,
EN61000-4-5, EN61000-4-8, EN61000-4-11, EN61347-2-13, EN62031, EN60968,
EN62471, 89/336/CEE, 93/68/CEE, 2002-95-CE

Peso / Weight: 1,3 kg

Materiale del Corpo: Alluminio
Material

Fonte Luminosa: LED type Citizen COB
Light source

Fattore di potenza: >0,90
Power factor

Vita gruppo ottico: >50000Hrs (Ta=30°C @ L70)
LED life expectancy

IK: 05



DESCRIZIONE PRODOTTO/ Product description

TUBULAR LED 25

Il Faretto TUBULAR LED è in grado di produrre una luce focalizzata con differenti aperture angolari: 10°/24°/36°.
L'elevato indice di resa cromatica garantisce una maggiore brillantezza dei colori.

Con un design che si adatta allo stile di qualunque ambiente, questo faretto è appositamente pensato per l'illuminazione di spazi commerciali dove è necessario disporre di una luce che concentri l'attenzione sui prodotti esposti, come negozi, ristoranti, bar, supermercati o showroom. Può anche essere utilizzato come complemento decorativo e di illuminazione generale.

Inoltre, possiede una protezione da cortocircuito e protezione da sovratensione, mostrando elevate prestazioni di sicurezza. Il radiatore in alluminio con trattamento di ossidazione a getto di sabbia offre un'eccellente dissipazione del calore e resistenza alla corrosione.









TUBULAR LED 25

The TUBULAR LED spotlight is able to produce a focused light with different angular openings: 10° / 24° / 36°.
The high color rendering index >80 ensures greater color brilliance.

With a design that adapts to the style of any environment, this spotlight is specially designed for lighting commercial spaces where it is necessary to have a light that focuses on the products on display, such as shops, restaurants, bars, supermarkets or showrooms. It can also be used as a decorative complement and for general lighting.

Furthermore, it has a short-circuit and overvoltage protection, showing high safety performance. The aluminum radiator with sand jet oxidation treatment offers excellent heat dissipation and corrosion resistance.

DETTAGLI / Details

Finitura Finishing	Codice Code	Temperatura colore Color Temperature	Codice Code	Ottiche Optics	Codice Code
 Bianco opaco White matt	8	 Bianco neutro Neutral white	4000K N		10°
 Nero opaco Black matt	9	 Bianco caldo Warm white	3000K W		24°
		 Meat Meat	P		36°

DIMENSIONI / Sizes

